

**DECLARATION OF PERFORMANCE**  
**No DWU 13/A/20**

**ENERPOR**

1. Unique product type identification code:

***EPS P 100 030 FOUNDATIONS***  
***EPS-EN 13163-T2-L3-W3-S<sub>b</sub>5-P10-BS150-CS(10)100-DS(N)5-DS(70,-)2-WL(T)1***

2. Intended use/es:

***Thermal insulation in buildings***

3. Manufacturer:

***„ENERPOR” Sp z o.o. 25-620 Kielce ul. Kolberga 11***

**MANUFACTURING PLANT:**

***„ENERPOR” Sp z o.o. 25-620 Kielce ul. Kolberga 11***

4. System(s) of assessment and verification of constancy of performance:

***System 3***

5. Harmonised standard:

***PN-EN 13163+A1:2015-03***

Notified body or bodies:

***Polskie Centrum Badań i Certyfikacji S.A.(1434)***  
***Instytut Techniki Budowlanej (1488)***

6. Declared performance:

Table no. 1

Declared thermal resistance  $R_D$  [ $m^2 \cdot K/W$ ]:

<b><i>d [mm]</i></b>	<b><i>50</i></b>
<b><i>R<sub>D</sub></i></b>	<b><i>1,65</i></b>

**DECLARATION OF PERFORMANCE**  
**No DWU 13/A/20**

**ENERPOR**

Table no. 2

<i>Essential characteristics</i>	<i>Performance</i>	<i>Declared class/level/ NPD<sup>a)</sup></i>	<i>Harmonised technical specification</i>
Thermal resistance	<i>Thermal resistance and thermal conductivity</i>	<i>R<sub>D</sub> – table no 1 λ<sub>D</sub> = 0,030 W/m·K</i>	<b>PN-EN 13163 +A1:2015-03</b>
	<i>Thickness</i>	<i>T2 d<sub>N</sub> - table no 1</i>	
<i>Reaction to fire</i>	<i>Reaction to fire</i>	<i>E</i>	
<i>Durability of reaction to fire against heat, weathering, ageing/degradation</i>	<i>Durability of properties<sup>b)</sup></i>	<i>NPD</i>	
<i>Durability of thermal resistance against heat, weathering, ageing/degradation</i>	<i>Thermal resistance – thermal Conductivity<sup>c)</sup></i>	<i>R<sub>D</sub> – table no 1 λ<sub>D</sub> = 0,030 W/m·K</i>	
	<i>Durability of properties</i>	<i>NPD</i>	
<i>Compressive strength</i>	<i>Compressive stress at 10% deformation</i>	<i>CS(10)100</i>	
<i>Tensile/Flexural strength</i>	<i>Bending strength</i>	<i>BS150</i>	
	<i>Tensile strength perpendicular to faces</i>	<i>NPD</i>	
<i>Durability of compressive strength against ageing and degradation</i>	<i>Compressive creep</i>	<i>NPD</i>	
	<i>Resistance to freezing-thawing</i>	<i>NPD</i>	
	<i>Long term thickness reduction</i>	<i>NPD</i>	
<i>Water permeability</i>	<i>Long term water absorption by immersion Long term water absorption by diffusion</i>	<i>WL(T)1 (&lt;1%) NPD</i>	
<i>Water vapour permeability</i>	<i>Water vapour transmission</i>	<i>NPD</i>	
<i>Impact noise transmission index (for floors)</i>	<i>Dynamic stiffness</i>	<i>NPD</i>	
	<i>Thickness, d<sub>L</sub></i>	<i>NPD</i>	
	<i>Compressibility</i>	<i>NPD</i>	
<i>Continuous glowing combustion</i>	<i>Continuous glowing combustion<sup>d)</sup></i>	<i>NPD</i>	
<i>Release of dangerous substances to the indoor environment</i>	<i>Release of dangerous substances<sup>d)</sup></i>	<i>NPD</i>	

*NPD<sup>a)</sup> No performance determined, <sup>b)</sup> The fire performance of EPS does not deteriorate with time, <sup>c)</sup> Thermal conductivity of EPS Products does not change with time, <sup>d)</sup> European test methods are under development*

7. The performance of the product identified above is in accordance with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

in Kielce

**Dyrektor Produkcji**  
  
**Jacek Garbacz**

on 06.02.2020