

**DECLARATION OF PERFORMANCE**  
**No DOP 14/21**

**ENERPOR**

1. Unique product type identification code:

**EPS 200 035 PARKING**  
**EPS-EN 13163-T2-L3-W3-S<sub>b</sub>5-P10-BS250-CS(10)200-DS(N)5-DS(70,-)2-DLT(1)5**

2. Intended use/es:

**Thermal insulation in buildings**

3. Manufacturer:

**„ENERPOR” Sp z o.o. 25-620 Kielce ul. Kolberga 11**

**MANUFACTURING PLANT:**

**„ENERPOR” Sp z o.o. 25-620 Kielce ul. Kolberga 11**

4. System(s) of assessment and verification of constancy of performance:

**System 3**

5. Harmonised standard:

**EN 13163:2012+A1:2015**

Notified body or bodies:

**Polskie Centrum Badań i Certyfikacji S.A.(1434)**  
**Instytut Techniki Budowlanej (1488)**

6. Declared performance:

Table no. 1

Declared thermal resistance  $R_D$  [ $m^2 \cdot K/W$ ]:

<b>d [mm]</b>	<b>10</b>	<b>20</b>	<b>30</b>	<b>40</b>	<b>50</b>	<b>60</b>	<b>70</b>	<b>80</b>	<b>90</b>	<b>100</b>	<b>110</b>	<b>120</b>	<b>130</b>	<b>140</b>	<b>150</b>
<b>R<sub>D</sub></b>	0,25	0,55	0,85	1,10	1,40	1,70	2,00	2,25	2,55	2,85	3,10	3,40	3,70	4,00	4,25
<b>d [mm]</b>	<b>160</b>	<b>170</b>	<b>180</b>	<b>190</b>	<b>200</b>	<b>210</b>	<b>220</b>	<b>230</b>	<b>240</b>	<b>250</b>	<b>260</b>	<b>270</b>	<b>280</b>	<b>290</b>	<b>300</b>
<b>R<sub>D</sub></b>	4,55	4,85	5,10	5,40	5,70	6,00	6,25	6,55	6,85	7,10	7,40	7,70	8,00	8,25	8,50

**DECLARATION OF PERFORMANCE**  
**No DOP 14/21**

**ENERPOR**

Table no. 2

<i>Essential characteristics</i>	<i>Performance</i>	<i>Declared class/level/ NPD<sup>a)</sup></i>	<i>Harmonised technical specification</i>
Thermal resistance	<i>Thermal resistance and thermal conductivity</i>	<i>R<sub>D</sub> - table no 1 λ<sub>D</sub> = 0,035 W/m·K</i>	<i>EN 13163:2012+A1:2015</i>
	<i>Thickness</i>	<i>T2 d<sub>N</sub> - table no 1</i>	
<i>Reaction to fire</i>	<i>Reaction to fire</i>	<i>E</i>	
<i>Durability of reaction to fire against heat, weathering, ageing/degradation</i>	<i>Durability of properties<sup>b)</sup></i>	<i>NPD</i>	
<i>Durability of thermal resistance against heat, weathering, ageing/degradation</i>	<i>Thermal resistance - thermal Conductivity<sup>c)</sup></i>	<i>R<sub>D</sub> - table no 1 λ<sub>D</sub> = 0,035 W/m·K</i>	
	<i>Durability of properties</i>	<i>NPD</i>	
<i>Compressive strength</i>	<i>Compressive stress at 10% deformation</i>	<i>CS(10)200</i>	
<i>Tensile/Flexural strength</i>	<i>Bending strength</i>	<i>BS250</i>	
	<i>Tensile strength perpendicular to faces</i>	<i>NPD</i>	
<i>Durability of compressive strength against ageing and degradation</i>	<i>Compressive creep</i>	<i>NPD</i>	
	<i>Resistance to freezing-thawing</i>	<i>NPD</i>	
	<i>Long term thickness reduction</i>	<i>NPD</i>	
<i>Water permeability</i>	<i>Long term water absorption by immersion</i>	<i>NPD</i>	
	<i>Long term water absorption by diffusion</i>	<i>NPD</i>	
<i>Water vapour permeability</i>	<i>Water vapour transmission</i>	<i>NPD</i>	
<i>Impact noise transmission index (for floors)</i>	<i>Dynamic stiffness</i>	<i>NPD</i>	
	<i>Thickness, d<sub>L</sub></i>	<i>NPD</i>	
	<i>Compressibility</i>	<i>NPD</i>	
<i>Continuous glowing combustion</i>	<i>Continuous glowing combustion<sup>d)</sup></i>	<i>NPD</i>	
<i>Release of dangerous substances to the indoor environment</i>	<i>Release of dangerous substances<sup>d)</sup></i>	<i>NPD</i>	

*NPD<sup>a)</sup> No performance determined ,<sup>b)</sup> The fire performance of EPS does not deteriorate with time ,<sup>c)</sup> Thermal conductivity of EPS Products does not change with time ,<sup>d)</sup> European test methods are under development*

7. The performance of the product identified above is in accordance with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

in Kielce

*Dyrektor Produkcji*  
  
**Jacek Garbacz**

on 12.02.2021